

XL-TRACE EDGE SELF-REGULATING HEATING CABLE



nVent RAYCHEM XL-Trace Edge self-regulating trace heating cables provide energy efficient and easy to use solutions for pipe freeze protection and flow maintenance of grease waste lines (above and below ground) and fuel lines (above ground).

FEATURES

Simple to design

Easy to install: cut to length, meter marks, fast RayClic cold connection system

Energy efficient and safe: self-regulating cable, advanced energy saving controls, no cable overheating possible, suitable for plastic pipes

Reliable during long life: 10 year extended product warranty available, maintenance free

SPECIFICATIONS

Min Installation Temperature: 0 °F

Ground Path Type: Braid

Catalog Number	Item Name	Supply Voltage	Nominal Power Output @ 40°F, 120V	Nominal Power Output @ 40°F, 240V	Outer Jacket Material	Max Circuit Length	Max Continuous Exposure Temperature, Power Off
2000002607	5XLE1-CR	120 V	5 W/ft	W/ft	Modified Polyolefin	287 ft	185 °F
2000002608	5XLE2-CR	208 – 277 V	W/ft	5 W/ft	Modified Polyolefin	584 ft	185 °F
2000002609	8XLE1-CR	120 V	8 W/ft	W/ft	Modified Polyolefin	233 ft	185 °F
2000002610	8XLE2-CR	208 – 277 V	W/ft	8 W/ft	Modified Polyolefin	452 ft	185 °F
2000002611	5XLE1-CT	120 V	5 W/ft	W/ft	Fluoropolymer	287 ft	185 °F
2000002612	5XLE2-CT	208 – 277 V	W/ft	5 W/ft	Fluoropolymer	584 ft	185 °F
2000002613	8XLE1-CT	120 V	8 W/ft	W/ft	Fluoropolymer	233 ft	185 °F
2000002614	8XLE2-CT	208 – 277 V	W/ft	8 W/ft	Fluoropolymer	452 ft	185 °F

Catalog Number	Item Name	Supply Voltage	Nominal Power Output@ 40°F, 120V	Nominal Power Output@ 40°F, 240V	Outer Jacket Material	Max Circuit Length	Max Continuous Exposure Temperature, Power Off
P000000793	12XL2-CR	208 – 277 V	W/ft	12 W/ft	Modified Polyolefin	360 ft	185 °F
P000000794	12XL2-CT	208 – 277 V	W/ft	12 W/ft	Fluoropolymer	360 ft	185 °F
2000002864	3XLE1-CR	120 V	3 W/ft	W/ft	Modified Polyolefin	368 ft	185 °F
2000002865	3XLE2-CR	208 – 277 V	W/ft	3 W/ft	Modified Polyolefin	642 ft	185 °F

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

Tel +1.800.545.6258
 Fax +1.800.527.5703
thermal.info@nvent.com

Europe, Middle East, Africa

Tel +32.16.213.511
 Fax +32.16.213.604
thermal.info@nvent.com

Asia Pacific

Tel +86.21.2412.1688
 Fax +86.21.5426.3167
cn.thermal.info@nvent.com

Latin America

Tel +1.713.868.4800
 Fax +1.713.868.2333
thermal.info@nvent.com



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER