

STYLE 5481

Style 5481 is 100% glass fiber, braided round in construction, supplied dry, but also available with a graphite finish upon request.

Style 5481 is usually found on static sealing or gasketing services where a round packing is needed. This product can also be used for expansion joint packing in boilers and furnaces, furnace door seals, coke oven door jam seals, sealing strainers in distillation columns, and gasketing around doors of wood-burning stoves (may require rope).

Style 5481 resists organic solvents, most acids, and mild alkalis. It has higher resistance to heat, does not burn or smolder, is dimensionally stable, is soft and flexible, has excellent insulating characteristics, has excellent electrical properties, and it retains its strength at elevated temperatures.

Style 5481 has been accepted as a substitute for asbestos materials by MSHA - Acceptance Number 092283GI. The product complies with all the requirements of Title 30, CFR, Chapter I, Part 18, Appendix II (figures 8, 9, and 10) regarding compression, flammability, and explosion.

| | |
|---------------------|---|
| TEMPERATURE | To +1000°F(+538°C) |
| PH RANGE | 2 – 11 |
| PRESSURE | 10 psi (1 Bar) Static |
| CONSTRUCTION | Braid-Over-Braid Sizes 1/8" – 2 1/2" Available in Round-Braid Diameters |