

### 1. Identification

**Product identifier** Gylon® Style 3510 & Gylon® EPIX™ Style 3510 EPX

**Other means of identification**

**Product code** 35100, 35103, 35103EPX

**Recommended use** Gasket Material

**Recommended restrictions** Maximum Service Temperature should not exceed 500°F

#### Manufacturer/Importer/Supplier/Distributor information

##### Manufacturer

**Company name** Garlock Sealing Technologies, LLC

**Address** 1666 Division Street  
Palmyra, NY 14522  
United States

**Telephone** M-F 9:00AM-4:00PM 315-597-4811  
FAX 315-597-3039

**E-mail** GSTSDS@garlock.com

**Emergency phone number** 315-597-4811

### 2. Hazard(s) identification

**Physical hazards** Not classified.

**Health hazards** Not classified.

**Environmental hazards** Not classified.

**OSHA defined hazards** Not classified.

#### Label elements

**Hazard symbol** None.

**Signal word** None.

**Hazard statement** The mixture does not meet the criteria for classification.

**Precautionary statement**

**Prevention** Observe good industrial hygiene practices.

**Response** Wash hands after handling.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of waste and residues in accordance with local authority requirements.

**Hazard(s) not otherwise classified (HNOC)** None known.

**Supplemental information** OSHA Hazard Communication Standard (29 CFR 1910.1200) requirements for Safety Data Sheets do not apply to the product(s) described in this document. This product is excluded in the regulation as an Article.

Heating PTFE to temperatures in excess of 500° F can evolve toxic fluorine compounds. Additional information concerning PTFE is available in the "Guide to the Safe Handling of Fluoropolymer Resins" published by the Fluoropolymers Division of the Society of the Plastics Industry, Inc.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Barium Sulfate		7727-43-7	50 - < 60
Polytetrafluoroethylene (PTFE)		9002-84-0	40 - < 50
Silica - Crystalline, Quartz		14808-60-7	< 0.5

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

<b>Inhalation</b>	No specific intervention is indicated as the product is not likely to be hazardous by inhalation. Consult a physician if necessary. If exposed to fumes from overheating or combustion, move to fresh air. Consult physician if symptoms persist.
<b>Skin contact</b>	The product is not likely to be hazardous by skin contact, but cleansing the skin after use is advisable.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	No specific intervention is indicated, as product is not likely to be hazardous by ingestion. Consult a physician if necessary.
<b>Most important symptoms/effects, acute and delayed</b>	Direct contact with eyes may cause temporary irritation.
<b>Indication of immediate medical attention and special treatment needed</b>	Treat symptomatically.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	Hydrogen fluoride fumes emitted during a fire can react with water to form hydrofluoric acid. Wear neoprene gloves when handling refuse from fire
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	No unusual fire or explosion hazards noted.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	None known.
<b>Methods and materials for containment and cleaning up</b>	None necessary.
<b>Environmental precautions</b>	None known.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Avoid grinding, abrading or other mechanical actions. Dust generated from this material must be managed by wet wiping or vacuuming with HEPA filtration equipped vacuum cleaners. Do not dry sweep or blow dust with compressed air. Avoid breathing dust. Avoid contamination of cigarettes or tobacco with dust from this material.
<b>Conditions for safe storage, including any incompatibilities</b>	Store in original tightly closed container.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Barium Sulfate (CAS 7727-43-7)	PEL	5 mg/m <sup>3</sup>	Respirable fraction.
		15 mg/m <sup>3</sup>	Total dust.
Silica - Crystalline, Quartz (CAS 14808-60-7)	PEL	0.05 mg/m <sup>3</sup>	Respirable dust.

**US. OSHA Table Z-3 (29 CFR 1910.1000)**

Components	Type	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Silica - Crystalline, Quartz (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Inhalable fraction.
Silica - Crystalline, Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable.
Silica - Crystalline, Quartz (CAS 14808-60-7)	TWA	10 mg/m3	Total
		0.05 mg/m3	Respirable dust.

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Appropriate engineering controls** General ventilation normally adequate.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** As generally good practice, safety glasses with side shields are recommended when handling this product to prevent eye contact with particulate matter.

**Skin protection**

**Hand protection** When handling hot material, use heat resistant gloves. Glove selection must take into account any solvents and other hazards present.

**Other** Not normally needed.

**Respiratory protection** Use a particulate filter respirator for particulate concentrations exceeding the Occupational Exposure Limit.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance**

**Physical state** Solid.  
**Form** Sheets or Gaskets  
**Color** Off-white.

**Odor** None.

**Odor threshold** Not available.

**pH** Not Applicable

**Melting point/freezing point** 620.6 °F (327 °C) / 2876 °F (1580 °C) estimated

**Initial boiling point and boiling range** Not Applicable

**Flash point** Not Applicable

**Evaporation rate** Not Applicable

**Flammability (solid, gas)** Not available.

**Upper/lower flammability or explosive limits**

**Flammability limit - lower (%)** Not Applicable

**Flammability limit - upper (%)** Not Applicable

**Explosive limit - lower (%)** Not available.

**Explosive limit - upper (%)** Not available.

**Vapor pressure** Not available.

**Vapor density** Not available.

**Relative density** Not available.

**Solubility(ies)**

**Solubility (water)** Not Soluble

**Partition coefficient (n-octanol/water)** Not Applicable

**Auto-ignition temperature** 968 - 1040 °F (520 - 560 °C)

**Decomposition temperature** > 500 °F (> 260 °C)

**Viscosity** Not Applicable

**Other information**

**Specific gravity** 2.85

**10. Stability and reactivity**

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

**Possibility of hazardous reactions** No dangerous reaction known under conditions of normal use.

**Conditions to avoid** Keep away from heat, sparks and open flame.

**Incompatible materials** Incompatible or can react with finely divided metal powders (e.g. aluminum and magnesium), molten alkali metals, and potent oxidizers like fluorine and related compounds like chlorine trifluoride. Contact with incompatibles can cause fire or explosion.

**Hazardous decomposition products** Composition of by-products from the result of a fire or thermal decomposition will vary depending on the specific conditions. Hazardous gases/vapors possibly evolved include smoke, hydrogen fluoride, carbonyl fluoride, perfluorocarbon olefins and carbon monoxide. There may be others unknown to us.

**11. Toxicological information**

**Information on likely routes of exposure**

**Inhalation** No adverse effects due to inhalation are expected.

**Skin contact** No adverse effects due to skin contact are expected.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical and toxicological characteristics** Direct contact with eyes may cause temporary irritation.

**Information on toxicological effects**

**Acute toxicity** No effects due to exposure to the product are anticipated. If exposed to thermal decomposition products of the PTFE, temporary symptoms of polymer fume fever, a temporary flu-like illness with chills, fever, and sometimes cough, of approximately 24 hours duration may arise. There are some reports in the literature of persistent pulmonary effects in individuals, especially smokers, who have repeated episodes of polymer fume fever. Because of complicating factors, such as mixed exposures and smoking history, these findings are uncertain. Small amounts of carbonyl fluoride and hydrogen fluoride may also be evolved when PTFE is overheated or burned.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

**Serious eye damage/eye irritation** Direct contact with eyes may cause temporary irritation.

## Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

### IARC Monographs. Overall Evaluation of Carcinogenicity

Polytetrafluoroethylene (PTFE) (CAS 9002-84-0) 3 Not classifiable as to carcinogenicity to humans.

Silica - Crystalline, Quartz (CAS 14808-60-7) 1 Carcinogenic to humans.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Silica - Crystalline, Quartz (CAS 14808-60-7) Cancer

### US. National Toxicology Program (NTP) Report on Carcinogens

Silica - Crystalline, Quartz (CAS 14808-60-7) Known To Be Human Carcinogen.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

**Specific target organ toxicity - single exposure** Not classified.

**Specific target organ toxicity - repeated exposure** Not classified.

**Aspiration hazard** Not an aspiration hazard.

## 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Barium Sulfate (CAS 7727-43-7)		
<b>Aquatic</b>		
Crustacea	EC50 Tubificid worm (Tubifex tubifex)	28.61 - 38.03 mg/l, 48 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions** Not available.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations.

**Contaminated packaging** Not available.

## 14. Transport information

### DOT

Not regulated as dangerous goods.

### IATA

Not regulated as dangerous goods.

### IMDG

Not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

## 15. Regulatory information

### US federal regulations

All components are on the U.S. EPA TSCA Inventory List.  
This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### TSCA Chemical Action Plans, Chemicals of Concern

Polytetrafluoroethylene (PTFE) (CAS 9002-84-0) Long-Chain Perfluorinated Chemicals (PFCs) Action Plan

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Barium Sulfate (CAS 7727-43-7) Listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Silica - Crystalline, Quartz (CAS 14808-60-7) Cancer  
lung effects  
immune system effects  
kidney effects

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SARA 302 Extremely hazardous substance

Not listed.

#### SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

### US state regulations

#### California Proposition 65



**WARNING:** California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### California Proposition 65 - CRT: Listed date/Carcinogenic substance

Silica - Crystalline, Quartz (CAS 14808-60-7) Listed: October 1, 1988

#### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Silica - Crystalline, Quartz (CAS 14808-60-7)

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Toxic Chemical Substances (TCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

<b>Issue date</b>	01-16-2018
<b>Revision date</b>	01-31-2018
<b>Version #</b>	02
<b>Further information</b>	This SDS supersedes the SDS dated: January 16, 2018
<b>Disclaimer</b>	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.